



ESX

ELECTRIC 36/48 VOLT

**2500 / 3000 / 3500 / 4000 / 4500 / 5000 lbs.
(1250 / 1500 / 1750 / 1815 / 2050 / 2270 kg)**

STANDARD SPECIFICATIONS

12/15S/17/20/22/25

Manufacturer's Designation		ESX 12	ESX 15S	ESX 15	ESX 17	ESX 20	ESX 22	ESX 25
Load Capacity / Rated Load	lbs(kg)	2500 (1500)	3000 (1500)	3000 (1500)	3500 (1750)	4000 (1815)	4500 (2050)	5000 (2270)
Height Overhead Guard	in(mm)	86.5 (2197)	86.5 (2197)	86.5 (2197)	86.5 (2197)	86.5 (2197)	86.5 (2197)	86.5 (2197)
Width Over Ties	in(mm)	40.3 (1024) / 42.2 (1072)	40.3 (1024) / 42.2 (1072)	40.3 (1024) / 42.2 (1072)	40.3 (1024) / 47.2 (1199)	40.3 (1024) / 47.2 (1199)	42.2 (1072)	42.2 (1072)
Right Angle Stack (Add Load Length and Clearance)	in(mm)	64.5 (1638)	64.5 (1638)	66.5 (1689)	69.0 (1753)	71.5 (1816)	73.5 (1867)	73.5 (1867)
Outside Turning Radius	in(mm)	51.6 (1311)	51.6 (1311)	53.6 (1361)	56.1 (1425)	58.6 (1488)	60.6 (1539)	60.6 (1539)
Travel Speed Loaded & Unloaded	mph (kph)	7.3 (11.7)	7.3 (11.7)	7.3 (11.7)	7.3 (11.7)	7.3 (11.7)	7.3 (11.7)	7.3 (11.7)
Power Unit	std. (optional)	36 volt	36 volt	36 volt (48 volt)	36 volt (48 volt)	36 volt (48 volt)	36 volt (48 volt)	36 volt (48 volt)

STANDARD FEATURES

- **CLARK Designed Multifunctional Control Handle**
- **Productivity Enhancement Package**
- **Electro-Hydraulic Fully Proportional Valve**
- **Enclosed Electromagnetic Brakes**
- **100% AC Motors**
- **Heavy Duty Drive Motors & Axles**
- **Rugged Upright and Carriage**
- **Fully Adjustable/Programmable Handset**



For more information on this model and full line of CLARK Forklifts, find your local CLARK Dealer at www.clarkmhc.com