

ECX

ELECTRIC 36/48 VOLT
COUNTERBALANCED FOUR-WHEEL
4000 / 5000 / 6000 / 6500 lbs. (2000 / 2500 / 3000 / 3000 kg)



STANDARD SPECIFICATIONS

20/25/30/32

Manufacturer's Designation		ECX 20	ECX 25	ECX 30	ECX 32
Load Capacity / Rated Load @ 24" LC	lbs(kg)	4000 (2000)	5000 (2500)	6000 (3000)	6500 (3000)
Height Overhead Guard	in(mm)	88 (2235)	88 (2235)	88 (2235)	88 (2235)
Width	in(mm)	41.9 (1063)	43.9 (1114)	43.9 (1114)	45.4 (1154)
Right Angle Stack (Add Load Length and Clearance)	in(mm)	86.8 (2204)	89.7 (2279)	91.3 (2319)	96.2 (2444)
Outside Turning Radius	in(mm)	70.2 (1783)	72.6 (1845)	73.9 (1877)	78.3 (1989)
Travel speed unloaded	mph (kph)	9.2 (14.8) / 11.3 (18.2)	9.1 (14.6) / 11.0 (17.7)	8.7 (14.0) / 10.8 (17.4)	8.0 (12.9) / 10.4 (16.7)
Power Unit		36 volt / 48 volt	36 volt / 48 volt	36 volt / 48 volt	36 volt / 48 volt

STANDARD FEATURES

100% AC Technology • Enclosed motors • Advanced thermal protection for all motors and controls • Quiet, non-polluting operation • Hydrostatic power steering • Hydraulic cushioning in lift mechanism • Adjustable steering pylon • Large instrument dash display • Variety of lights, alarms and other options are available



For more information on this model and the full line of CLARK Forklifts, find you local CLARK Dealer at www.clarkmhc.com.