



C40

IC- PNEUMATIC LPG/DIESEL
 8000 / 9000 / 10,000 / 11,000 lbs.
 (4000 / 4500 / 5000 / 5500 kg)

STANDARD SPECIFICATIONS

C40/45/50s/55s

Manufacturer's Designation		C40D	C45D	C50sD	C55sD	C40L	C45L	C50sL	C55sL
Load Capacity / Rated Load	lbs(kg)	8000 (4000)	9000 (4500)	10,000 (5000)	11,000 (5500)	8000 (4000)	9000 (4500)	10,000 (5000)	11,000 (5500)
Height Overhead Guard	in(mm)	91.5(2324)	91.5 (2324)	90.9 (2310)	90.9 (2310)	91.5 (2324)	91.5 (2324)	90.9 (2310)	90.9 (2310)
Width	in(mm)	55.1(1400)	55.1 (1400)	68.6 (1742)	68.6 (1742)	55.1 (1400)	55.1 (1400)	68.6 (1742)	68.6 (1742)
Right Angle Stack (add load length & clearance)	in(mm)	134.5(3416)	135.9 (3451)	135.9 (3451)	144.4 (3669)	108.5 (2755)	108.5 (2755)	112.0 (2845)	112.0 (2845)
Outside Turning Radius	in(mm)	111.9(2843)	113.3 (2878)	119.4 (3032)	120.9 (3071)	111.9 (2843)	113.3 (2878)	119.4 (3032)	120.9 (3071)
Travel Speed Loaded / Unloaded	mph (kph)	13.7/14.4 (22/23.2)	13.5/14.4 (21.7/23.2)	12.6/13.4 (20.3/21.6)	12.6/13.4 (20.3/21.6)	12.6/13.5 (20.3/21.7)	12.6/13.5 (20.3/21.7)	11.8/12.5 (19.0/20.1)	11.8/12.5 (19.0/20.1)
Power Unit	HP(KW) @ rpm	Deutz TD3.6 74.3 (85.4) @ 2200	Deutz TD3.6 74.3 (85.4) @ 2200	Deutz TD3.6 74.3 (85.4) @ 2200	Deutz TD3.6 74.3 (85.4) @ 2200	PSI - 4X 109.9 (82) @ 2400	PSI - 4X 109.9 (82) @ 2400	PSI - 4X 109.9 (82) @ 2400	PSI - 4X 109.9 (82) @ 2400

STANDARD FEATURES

- Deutz TD3.6 Diesel Engine • EPA Compliant • Standard Triple and Hi-Lo Uprights • Full Range of Lift Heights • High Visibility “Silent Staging” Uprights • Two Speed Auto-Shift Transmission • Wet Disc Brakes • Planetary Drive Axle • Square Fin Radiator • High Capacity Cooling System • Hood Mounted Control Levers • Power Steering • Tilt Steering Wheel • Grab Bar Handle with Horn • Traction Disable Seat Switch • Operator Presence System • Orange Seatbelt



For more information on this model and full line of CLARK Forklifts, find your local CLARK Dealer at www.clarkmhc.com