



CGC

IC- CUSHION LPG

8,000 / 10,000 / 12,000 lbs.

(4,000 / 5,000 / 5,500 kg)

STANDARD SPECIFICATIONS

40/50/55

Manufacturer's Designation		CGC40	CGC50	CGC55
Load Capacity / Rated Load	lbs(kg)	8,000 (4,000)	10,000 (5,000)	12,000 (5,500)
Height Overhead Guard	in(mm)	87.2 (2215)	87.2 (2215)	87.2 (2215)
Width	in(mm)	50.8 (1290)	54.8 (1392)	54.8 (1392)
Right Angle Stack (add load length & clearance)	in(mm)	STD 106.7 (2710) / TSU 107.5 (2731)	STD 116.0 (2946) / TSU 116.8 (2967)	STD 118.3 (3005) / TSU 119.1 (3025)
Outside Turning Radius	in(mm)	89.4 (2270)	98.2 (2494)	99.9 (2537)
Travel Speed Loaded / Unloaded	mph (kph)	12.2/12.5 (19.6/20.1)	12.1/12.4 (19.5/20.0)	11.7/12.2 (18.8/19.6)
Power Unit	HP(KW) @ rpm	PSI-4X 4.3L 110 (82) @ 2400	PSI-4X 4.3L 110 (82) @ 2400	PSI-4X 4.3L 110 (82) @ 2400

STANDARD FEATURES

- PSI-4X 4.3L V6 Engine • EPA Compliant • Standard, Triple and Quad Uprights • Full Range of Lift Heights • High Visibility "Silent Staging" Uprights • Single Speed Powershift Transmission on CGC40 and Two Speed Powershift on the CGC50-55 • Cowl Mounted Levers • Power Steering • Tilt Steering Wheel • Rear Handle with Horn Button • Full Suspension Vinyl Safety Seat • Orange Seatbelt • Traction Disable Seat Switch • Operator Presence System • Power Assisted Disc Brakes • Open Core Radiator • High Air Intake • Heavy Duty Air Cleaner • Tow Pin • Automatic Engine Shutdown System



For more information on this model and full line of CLARK Forklifts, find your local CLARK Dealer at www.clarkmhc.com