



# GTS

IC- PNEUMATIC LPG  
 4000 / 5000 / 6000 / 6600 lbs.  
 (2000 / 2500 / 3000 / 3300 kg)

## STANDARD SPECIFICATIONS

## GTS20/25/30/33

Manufacturer's Designation		GTS20L	GTS25L	GTS30L	GTS33L
Load Capacity / Rated Load	lbs(kg)	4000 (2000)	5000 (2500)	6000 (3000)	6600 (3300)
Height Overhead Guard	in(mm)	85.4 (2170)	85.4 (2170)	85.8 (2180)	85.8 (2180)
Width	in(mm)	46.7 (1185)	46.7 (1185)	49.2 (1250)	49.2 (1250)
Right Angle Stack (add load length & clearance)	in(mm)	108.5 (2755)	112.0 (2845)	116.3 (2955)	117.7 (2990)
Outside Turning Radius	in(mm)	90.2 (2290)	93.7 (2380)	97.6 (2480)	98.9 (2510)
Travel Speed Loaded / Unloaded	mph (kph)	10.7 (17.2) 11.4 (18.3)	10.5 (16.9) 11.4 (18.3)	11.4 (18.3) 12.1 (19.5)	12.2 (19.6) 12.8 (20.6)
Power Unit	HP(KW) @ rpm	PSI- 4X 64 (47.9) @ 2500	PSI- 4X 64 (47.9) @ 2500	PSI- 4X 64 (47.9) @ 2500	PSI- 4X 64 (47.9) @ 2500

## STANDARD FEATURES

- PSI 2.4L Balanced Engine • EPA Compliant LPG Fuel System • Standard, Triple and Hi-Lo Uprights • Single Speed Powershift Transmission • Separate Transmission and Axle • Wet Disc Brakes
- Headlights on Overhead Guard • Hood Mounted Control Levers • Power Steering • Tilt Steering Wheel • Full- Suspension Vinyl Seat • Orange Seat Belt • Traction Disable Seat Switch • Operator Presence System • Hand Parking Brake • Raised Air Intake • Square Fin Radiator • High Capacity Cooling System • Automatic Engine Shutdown System



For more information on this model and full line of CLARK Forklifts, find your local CLARK Dealer at [www.clarkmhc.com](http://www.clarkmhc.com)